

**Product Name :**  
B.o.d. Incubator

**Product Code :**  
SCIENTIFIC0023



## Description :

B.o.d. Incubator

## Technical Specification :

B.O.D. Incubator are suitable for preservation of vaccines, insulin, liver extracts, chemicals etc. and to make biochemical oxygen demand determination.

Construction : The low temperature incubator is made of double walled S.S sheet finished with epoxy based powder coated paint, inner chamber is made of highly polished stainless steel / anodized aluminium. Two doors are provided, inner door is made of transparent acrylic for inspecting specimens outer door is insulated and is fitted with magnetic tape with lock and key. Temperature range from 2°C to 32°C with an accuracy of +1°C provided with two air circulating fans, high performance compressor, cooling coils, heating elements. Digital temperature control and display is also

fitted with a door operated illumination and a castor wheel for easy mobility

<p>Cu. Ft. : 5.1 Height mm : 825 Width mm : 395 Depth mm : 415</p> <p>Inner chamber : Aluminium</p>
<p>Cu. Ft. : 5.1 Height mm : 825 Width mm : 395 Depth mm : 415</p> <p>Inner chamber : S.S</p>
<p>Cu. Ft. : 5 Height mm : 800 Width mm : 380 Depth mm : 380</p> <p>Inner chamber : Aluminium</p>
<p>Cu. Ft. : 5 Height mm : 800 Width mm : 380</p>

<p>Depth mm : 500</p> <p>Inner chamber : S.S</p>
<p>Cu FT : 10</p> <p>Height mm : 800</p> <p>Width mm : 500</p> <p>Depth mm : 500</p> <p>Inner chamber : Aluminium</p>
<p>Cu FT : 10</p> <p>Height mm : 800</p> <p>Width mm : 500</p> <p>Depth mm : 500</p> <p>Inner chamber : S.S</p>
<p>Cu FT : 12</p> <p>Height mm : 900</p> <p>Width mm : 600</p> <p>Depth mm : 500</p> <p>Inner chamber : Aluminium</p>
<p>Cu FT : 12</p> <p>Height mm : 900</p> <p>Width mm : 600</p> <p>Depth mm : 500</p> <p>Inner chamber : S.S</p>



# LAB ENGINEERING

## Elab Engineering Equipments Manufacturers