

Product Name :
AUTOCLAVE VERTICAL TRIPLE WALLED HIGH
PRESSURE FOR DRY STERLIZATION

Product Code :
BMHCE0065



Description :

AUTOCLAVE VERTICAL TRIPLE WALLED HIGH PRESSURE FOR DRY STERLIZATION

Technical Specification :

• "SD" Triple-walled High Pressure Autoclave are used where Dry Sterilization is required.

• Triple-walled High Pressure Autoclave are most ideal for critical applications requiring assured and reliable total destruction of all living micro-organisms.

• It is used for sterilizing of surgical instruments, dressing material, linen, rubber, plastic material, injection liquids by means of steam under pressure of 15 to 20 psi. (adjustable).

SALENT FEATURES & CONSTRUCTION :

Used for Dry Sterilization

Steam Jacket & Outer wall made of S. S. 304 Grade

Water Level Indicator

Lid Closing by Radial Locking System

Sealing of Lid by Neoprene Rubber Gasket

Lid is fitted with Pressure Gauge, Spring Loaded Safety Valve

Operating range from 10psi to 20psi pressure

Hydraulically Tested up to 40 psi

Operating Temperature up to 150°C

Tested up to 2.5 times of required Pressure

Voltage: 220 Volts AC (50 Hz)

@ LAB ENGINEERING
Elab Engineering Equipments Manufacturers
