

Product Name :
Portable Wheatstone Bridge

Product Code :
EELELABT10020



Description :

Portable Wheatstone Bridge

Technical Specification :

This bridge is fully portable with a built in sensitive Galvanometer and a dry battery. The bridge is extremely useful for resistance measurements with a fair degree of precision.

Series Arm :

- There are 4 decades of 10×1 , 10×10 , 10×100 and 10×1000 ohms.

Range Multiplier :

- A single rotary switch furnishes 7 range multipliers of $\times 1000$, $\times 100$, $\times 10$, $\times 1$, $\times 0.1$, 0.01 and 0.001 .

Range of Measurement :

- Ohm to 1.11 mega ohms.

Battery :

- A dry battery of 4.5 volts is built-in provision is there for using external battery for measuring high resistances.

Galvanometer :

The bridge can be supplied with types of built-in galvanometer. Student galvanometer of M.O. 65 model, and of sensitivity 10 microamperes/mm. Taut suspension galvanometer of coil resistance 100 ohms and sensitivity of 0-5 microampere per mm and with a mechanical coil locking device and a zero adjuster. In both models, external more sensitive galvanometer such as our spot reflecting galvanometer as above can be used for greater discrimination and accurate null point.

Resistance Coil :

- Manganin coil which are non inductivity wound, aged and properly varnished are used.

Push Button :

- Two push buttons for battery and galvanometer are provided.

Accuracy :

- Both series and ratio coils are adjusted to an accuracy of better than 0.05%
- Overall Accuracy of measurements is better than + 0.1%
- With Students galvanometer of M.O. 65 model
- With Taut suspension galvanometer.

 **LAB ENGINEERING**

Elab Engineering Equipments Manufacturers