© LAB ENGINEERING

Email:

purchase@elabengineeringequipments.com Phone: +91-9811375383

Product Name:

Microprocessor Conductivity/TDS Meter

Product Code: ELAB-ELC0011



Description:

Microprocessor Conductivity/TDS Meter

Technical Specification:

Microprocessor Conductivity/TDS Meter

Features:-

16 x 2 Line Alphanumeric LCD Display

Auto Temperature Compensation

Auto Ranging Facility

90 Samples Storage Facility

Printer Attachment Facility

Conductivity, TDS & Temp. Measurements

Microprocessor Conductivity/TDS Meter is a solid state instrument designed to provide the precise conductivity/TDS measurements.

The instrument uses the latest Microprocessor technology and advanced engineering techniques so as to give enhanced accuracy and reproducibility.

The system has user friendly prompts which guide you throughout the measurement process.

The system has 8 soft touch membrane type keys for ease of operation.

It has the storage facility for 90 samples, which are retained in the memory even when the system is switched OFF.

Provision has also been provided for attachment of centronix dot matrix printer so that any of the stored results can be printed.

The instrument is extremely useful for agriculture and soil analysis laboratories, swimming pools, water quality control in boiler feed water, water works department, fertilizer plants, petroleum refineries, breweries, water

purification plan	ts etc.	_	_	_	
Specifications:-	Parameter	Conductiviity	TDS	Temperature	
	Range Selection	Automatic	Automatic		
	Range	0-20, 0-200uS, 0-2,	0-20, 0-200 ppm,	0-100oC	
		0-	0-2,0-20,0-200		
		1			
		20, 0-200mS	ppt		
	Accuracy	±0.5% FS ±1 Digit	±1% FS ±1 Digit	0.1oC	
	Resolution	0.01 uS	0.01 ppm	0.1oC	
	Cell constant	Adjustable (Adjustable (0.05		
		0.05-10.5)	-10.5)		
	Temperature	Auto/Manual	Auto/Manual		
	compensation	(0-50oC)			
	Temperature	Adjustable (0.1-4.0%))Adjustable (0.1-4.0%)		
	Coefficient				
	Readout	16x2 Line Alphanumeric LCD display			
	Storage	Up to 90 Samples			
	Key board	8 soft touch membrar	8 soft touch membrane type keys		
	Printer Interface	Dot-Matrix Printer with Centronics Interface			
	Power	230V±10%AC,50Hz			
	Accessories	Conductivity/TDS Cell, Temperature probe, Dust Cover,			
		Instruction Manual			
		_			

© LAB ENGINEERING

Elab Engineering Equipments Manufacturers